

DESCRIPTION

- An interior, high solids, one part water based acrylic coating,
- Designed to deliver high performance results at a moderate price.
- Applies directly to most common substrates. Class "A" non-combustible, non-toxic, very low VOC.
- Exceptional performance against mold and mildew growth.
- Use in lieu of vinyl wall covering.

ADVANTAGES

- Very durable.
- 80% as hard as mild steel.
- Improves the strength of drywall.
- Significantly longer life cycle than vinyl wall covering.

10-YEAR WRITTEN PERFORMANCE WARRANTY

Against peeling, delaminating, cracking, and chalking.

10-YEAR WRITTEN MOLD/MILDEW WARRANTY

- High perm rate to achieve breathability.
- Engineered formulation which virtually eliminates food sources for organisms combined with a long-term mildewcide that provides excellent performance.
- Full details available by contacting Triarch.

SCRUBBABLE

- Not damaged by water.
- Most marks and scuffs removed after 7 – 10 days of curing, using a stiff scrub brush with liquid soap and water.

DESIGN OPTIONS

- Over twenty-five (25) textural effect/patterns and almost unlimited integral colors, both monochromatic and multi-color finishes.
- Call TRIARCH for samples or a design binder.

DELIVERY TIME

Quick ship, most small shipments leave the centrally located factory within 48 hours of an order.

FACTORY TRAINED APPLICATORS*

- Over 600 factory trained applicators available nationally and internationally.
- We offer training programs to help insure quality control and minimize installation time.

COST

- Most projects install from \$1.25 - \$4.00 per square foot.
- Actual job conditions, volume, wall elevations, and local labor may affect installed prices.

PRODUCT DATA

SPECIFICATIONS

- Water based acrylic
- Integral & Colorfast Pigments
- Barcol Hardness of 38
- ASTM E-84, Flame spread = 15
- Smoke contribution = 5
- FAR 25.853(b), FAA Vertical Burn
- After Flame Time <0.1 seconds
- ASTM E-96, English Wet Perms = 28
- Final dry film thickness of 20 mils
- Qualifies under LEEDS section 4.2 for low emitting material
- Conforms to CHPS-CA section 01350

SHIPPING AND STORAGE

- Shipped in 5 gallon plastic pails
- Protect from freezing
- Protect from heat over 100°F.
- Stack to maximum of three (3) pails high
- Two (2) year shelf life

APPLICATION

Roller or spray applied depending upon selected finish. Applied by factory trained applicators. Applicator's field manual is available from the factory.

* TRIARCH DOES NOT WARRANT, GUARANTEE, OR ASSUME LIABILITY FOR THE WORKMANSHIP OF THE APPLICATOR