

DESCRIPTION

- An interior, water-based, high solids, pure acrylic coating, designed to decorate faux finish effects with enhanced performance results.
- Applied directly to most common construction substrates.
- Class 'A' non-combustible, non-toxic, very low VOC.

ADVANTAGES

- Durable, abuse resistant, easily cleaned, low maintenance.
- Life cycle 8 -10 years with active use.

5-YEAR WRITTEN COATING INTEGRITY WARRANTY

5-YEAR WRITTEN MOLD/MILDEW WARRANTY

- Against mold and mildew growing on the surface of Faulux finish. See written warranty for detailed requirements.
- Full details are available by contacting Triarch.

SCRUBBABLE

- Not damaged by water.
- Most marks and scuffs removed after 7—10 days of curing, using a stiff scrub

brush with liquid soap and water.

DESIGN OPTIONS

Available in a variety of patterns (unlimited, integral colors, both monochromatic and multi-color finishes). Call TRIARCH for samples.

DELIVERY TIME

Quick ship. Smaller shipments leave the centrally located factory within 48 hours after a placed order. Customer samples and smaller order may take a little longer — up to 5-10 days.

INSTALLATION

Applied with traditional painter's tools. May require some decorative painting skills.

FACTORY TRAINED APPLICATORS*

Factory trained applicators available nationally, however, always request a mockup.

COST

Most projects install between \$.75 - \$3.50 per square foot, depending upon finish selected, actual job conditions, elevations, and local labor may affect installed prices.

PRODUCT DATA

SPECIFICATIONS

- Water based acrylic
- Integral and Colorfast Pigments
- ASTM E-84-95, Flame spread = 15
- Smoke Contribution = 0
- ASTM E-96B, English Wet Perms =20~
- ASTM D-3960 VOC, 1#/gal.
- ASTM D2488 Scrub> 2000 cycles
- Dry film thickness of 10 mils, depending upon pattern

SHIPPING AND STORAGE

- Packaged in either 1 or 5 gallon plastic pails
- Protect from freezing
- **Protect from heat over 100°F.**
- Stack to maximum of three (3) pails high.
- One (1) year shelf life.

APPLICATION

Wet application. Always obtain approval on mockup before doing the job. Finish selection will control application technique. May be spray applied, roller applied, or combination techniques. Sequence depends upon selected finish.

*** TRIARCH DOES NOT WARRANT, GUARANTEE, OR ASSUME LIABILITY FOR THE WORKMANSHIP OF THE APPLICATOR**

Triarch
P.O. Box 1014
One Energy Way
West Warwick, RI 02893
800-537-6111
www.triarchinc.com

This information conforms to the standard detail recommendations and specifications for the installation of Triarch products as of the date of publication of this document and is presented in good faith. Triarch assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Triarch. Triarch expressly disclaims all implied warranties, including without limitation, implied warranties of merchantability and fitness for a particular purpose.



A Division of Dryvit Systems, Inc.