

SPATULA STUHHI™

TRANSLUCENT VENETIAN PLASTER

T113

DESCRIPTION

An interior one part, lime and ground marble based thin coat plaster finish system, designed to deliver a sophisticated & decorative finish for the commercial and residential marketplace. Finish options include: gloss, matte, waxed, unwaxed, stencils, metallics, and multi color blends

SPATULA STUHHI ADVANTAGES

NO SPECIAL SUBSTRATE NEEDED

Applies to all clean, sound, unpainted drywall, concrete, masonry or wood substrates. Requires minimum of a level 4 or equivalent type drywall finish for the substrate.

10-YEAR WRITTEN WARRANTY

When entire system is applied, Spatula Stuhhi plaster carries a 10 year warranty against peeling delamination, cracking, and chalking.

INSTALLATION

Consists of a special primer (GEXXO™) and a 2 or 3 coat application process by trowel depending upon finish selected. Optional wax topcoat to seal

the surface is also available. Additional optional effects can include metallic and stencil effects.

MILDEW RESISTANT

High alkaline formula helps to prevent mold or mildew growth on the surface of the plaster.

DESIGN OPTIONS

Include a wide range of color options, as well as either a gloss (Classico) or various matte finishes (OPACO). Additional effects include an embedded stencil system, metallic, and multi color effects. Optional wax topcoat improves washability. Call TRIARCH for samples, color charts, or a design binder or visit our website at www.triarchinc.com.

DELIVERY TIME

Most orders leave the centrally located distributor within 2-3 days.

FACTORY TRAINING

Factory trained applicators available nationally.*

COST

Most projects install between \$5.00-\$10.00 per sq. foot; depending upon quantity, wall height, local labor rates, and color. Job conditions may also affect installed price.

PRODUCT DATA

SPECIFICATIONS

- Lime and marble based plaster
- Integral & colorfast pigments
- Ultraviolet, wet/dry, heat/chill no failures
- ASTM E-84, Flame spread = 8.5, Smoke contribution = 0.0
- Incombustible

SHIPPING AND STORAGE

- Shipped in 24 kilo pails (5 gallon pails)
- Pigment system shipped separately
- Protect from freezing
- Protect from heat over 100°F.
- 1 year shelf life

FINISH

Applied film thickness is approximately 10 mils. Finish must be trowel applied and be a multi coat system.

***TRIARCH DOES NOT WARRANT, GUARANTEE, OR ASSUME LIABILITY FOR THE WORKMANSHIP OF THE APPLICATOR.**

Triarch
P.O. Box 1014
One Energy Way
West Warwick, RI 02893
800-537-6111
www.triarchinc.com

This information conforms to the standard detail recommendations and specifications for the installation of Triarch products as of the date of publication of this document and is presented in good faith. Triarch assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Triarch. Triarch expressly disclaims all implied warranties, including without limitation, implied warranties of merchantability and fitness for a particular purpose.



A Division of Dryvit Systems, Inc.