

DESCRIPTION

- An interior, high solids, one part water based acrylic coating,
- Designed to deliver high performance results at a moderate price.
- Applies directly to most common substrates. Class “A” non-combustible, non-toxic, very low VOC.
- Exceptional performance against mold and mildew growth.
- Use in lieu of vinyl wall covering.

ADVANTAGES

The Duroplex Dimensional Metals 2 (DDM2) line offers exciting and unique finishes. Unlike many of the metallic finishes available on the market today, a DDM2 finish is “Duroplex” tough. DDM2 incorporates most of the performance characteristics associated with standard Duroplex finishes, scrub & abrasion resistant (8000 scrubs cycles), mildew resistant, class “A” flame & smoke, and a 10 year product warranty.

10-YEAR WRITTEN PERFORMANCE WARRANTY

Against peeling, delaminating, cracking, and chalking.

10-YEAR WRITTEN MOLD/MILDEW WARRANTY

- High perm rate to achieve breathability.
- Engineered formulation which virtually eliminates food sources for organisms

combined with Biophase® , a long-term mildewcide that provides unequaled performance (over three million square feet installed in tropical regions for ten [10] years without any trace of mildew).

- Full details available by contacting Triarch.

SCRUBBABLE

- Not damaged by water.
- Most marks and scuffs removed after 7 – 10 days of curing, using a stiff scrub brush with liquid soap and water.

DESIGN OPTIONS

Metallic Wash Options

- Inca Gold
- Rust
- Welder’s Arc
- Oxidation
- Electric Orange
- Stainless Steel

Standard Textural Options

- Sahara – orange peel texture
- Alexandria – a smooth textural effect with mottled metal shimmers
- Luxor – a heavily textured effect abraded by the sands of time
- Cairo – a hand rubbed, rough vertical grooved effect

FACTORY TRAINED APPLICATORS*

- Over 600 factory trained applicators available

nationally and internationally.

- We offer training programs to help insure quality control and minimize installation time.

PRODUCT DATA

SPECIFICATIONS

- Water based acrylic
- Integral & Colorfast Pigments
- Barcol Hardness of 38
- ASTM E-84, Flame spread = 15
- Smoke contribution = 5
- FAR 25.853(b), FAA Vertical Burn
- After Flame Time <0.1 seconds
- ASTM E-96, English Wet Perms = 28
- Final dry film thickness of 20 mils

SHIPPING AND STORAGE

- Shipped in 5 gallon plastic pails
- Protect from freezing
- Protect from heat over 100°F.
- Stack to maximum of three (3) pails high
- One (1) year shelf life

APPLICATION

Roller or spray applied depending upon selected finish.

*Triarch does not warrant, guarantee, or assume liability for the workmanship of the applicator.

Triarch
One Energy Way
West Warwick, RI 02893
800-537-6111
www.triarchinc.com

Printed in USA
©Triarch 2007

This information conforms to the standard detail recommendations and specifications for the installation of Triarch products as of the date of publication of this document and is presented in good faith. Triarch assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Triarch. Triarch expressly disclaims all implied warranties, including without limitation, implied warranties of merchantability and fitness for a particular purpose.



A Division of Dryvit Systems, Inc.